




TEMPERATURE RANGE

TN  **-2°C / +7°C (PC-PV)**

BT  **-24°C / -18°C (PC)**

BT  **-20°C / -10°C (PV)**

MAX CONDITION


TN  **43°C**  **60 UR%**

BT  **32°C**  **60 UR%**

BT  **32°C**  **60 UR%**

COMPANY
WITH QUALITY MANAGEMENT
SYSTEM CERTIFIED BY DNV
= ISO 9001:2000 =

1400 L - TAMPONE



Specifiche Tecniche - Specifications - Technische Daten - Données Techniques - Dato Técnicos

230 V / 50 Hz		RANGE	-2°C/+7°C	-24°C/-18°C	-2°C/+7°C PV	-20°C/-10°C PV
Codice prodotto Item code no	Produkt-Kode-Nr. Nr. de code du produit	inox*rosfr.St s/s*inox	8T0140INC.....	8T140IBC.....	8T140INV.....	8T140IBV.....
Lunghezza esterna Outside length	Aussenlänge Longueur extérieure	mm	1466	1466	1466	1466
Altezza Height	Höhe Hauteur	mm	2090	2090	2090	2090
Profondità Depth	Tiefe Profondeur	mm	800	800	800	800
Capacità Capacity	Inhalt Capacité	dm ³	1200	1200	1200	1200
Potenza frigorifera Refrigeration power	Kalorienleistung (Te:-10°C..-30°C/Tc :+45°C) Puissance frigorifique	kcal/h W	544 632	660 768	544 632	700 814
Fluido refrigerante Refrigerant fluid	Kältemittel Gas frigorigène		R 404A	R404A	R 404A	R404A
Potenza assorbita Absorbed power	Leistungsaufnahme Puissance absorbée	W / I max (A)	568/4.2	1117/7.8	568/4.2	1117/7.8
Consumo giornaliero/24h Daily consumption/24h	Tagesverbrauch/24h UNI EN 441-9 Consommation par jour/24h	kWh/24h	6,3	21.7	7.4	19.8
Resist. Sbrinamento Defrosting heater	Abtauheizung Resistance degivrage	W	600	600	600	600
Peso Weight	Gewicht Poids	Kg	230	235	240	245

